



SERVICE INSTRUCTION

SI0025 Rev NC

Page 1 of 1

EFFECTIVE DATE: This Service Instruction is effective August 7th, 2012.
SUBJECT: Window Safety Limitation Placard
MODELS AFFECTED: "CC11-100 OR CC11-160 S/N 00001 AND ON"
COMPLIANCE TIME: Compliance is Recommended
PURPOSE: Window Safety Limitation Placard Installation

PARTS LIST:

<u>PART</u>	<u>DESCRIPTION</u>	<u>QTY</u>
SC10950-023	MAXIMUM SPEED WINDOWS OPEN	1

INSTRUCTIONS:

1. If not already installed, the placard will be installed on the left side panel so that it is easily visible. Locate a position for the placard running along the top of the panel (where the forward throttle knob protrudes) forward of the front window latch.
2. Clean the surface of any dust or grease using a wet cloth and allow it to dry completely.
3. Remove the placard from the backing and apply to the surface, removing any bubbles.

MAXIMUM SPEED WINDOWS OPEN 81 MPH / 70 KTS.
WINDOWS MUST BE CLOSED FOR TAKEOFF AND LANDING.
ONLY ONE WINDOW MAY BE OPEN IN FLIGHT AT A TIME.

NOTE: The placard should be aligned so that it can be read from the pilot's seat and should not be located where it will interfere with the throttle controls or the window and latch.

If you are no longer in possession of this aircraft, please forward this information to the present owner/operator and notify Cub Crafters, Inc. of the address of the current owner to:

Cub Crafters, Inc.
1918 S. 16th Avenue
Yakima, WA 98903.
1-877-484-7865 or 1-509-248-9491
support@cubcrafters.com

Please include the aircraft registration number, serial number, current name, and address of the owner and/or operator.